Cabinets

Gallagher Cabinets are secure enclosures for Gallagher Controllers and I/O Devices.

Gallagher Cabinets are designed to house multiple Gallagher products. There are two cabinet sizes available, accommodating either one or two printed circuit board (PCB) footprints. Mounting options allow combinations of various PCB types to be installed.

1. Gallagher Single Cabinet

Manufactured from a strong polycarbonate/ABS plastic alloy, the Gallagher Single Cabinet has a UL94 flame rating of HB. It provides one footprint for Gallagher Controllers and I/O PCBs.

One cabinet can house a combination of the following

- 1x Gallagher Controller 6000
- 1x Gallagher 4H, 8H, 4R or 8R Module
- 1x Gallagher Controller 6000 I/O Mounting Plate
- 1x Half Footprint Mounting Plate
- 1x Tamper Board
- 1x Gallagher HBUS 16 In 16 Out Board. A second HBUS 16 In 16 Out Board can be installed in a single cabinet using standoffs

2. Gallagher I/O Accessory Single Cabinet

A variation of the Gallagher Single Cabinet, the Gallagher I/O Accessory Single Cabinet is a secure enclosure providing one footprint for Gallagher devices. This cabinet is supplied with a mounting plate and tamper board.

The input/output expansion boards are modular, designed to be mounted on the mounting plate in the following combinations:

- Up to 4x Gallagher HBUS 8 In Boards or Gallagher Door Modules, or
- Up to 2x HBUS 8 In 4 Out Boards, or
- 1x HBUS 8 In 4 Out Board and up to 2x HBUS 8 In Boards or Gallagher Door Modules

3. Gallagher Dual Cabinet

The Gallagher Dual Cabinet is a secure steel enclosure accommodating two footprints, doubling the housing capacity for any combination of Gallagher PCBs. When the PCB is installed, optical tamper protection is provided for both the front and rear of the Cabinet. The Cabinet is also available with an optional 8 Amp power supply which has visible indicators for 'low mains' and 'low battery' power monitoring. A separate mounting plate and tamper board is available to enable Gallagher GBUS I/O Devices (excluding the Gallagher High Density I/O Interface) to be fitted with optical tamper protection.

All devices must be mounted in the Cabinets following the installation instructions to comply with international emission standards such as RCM. CE and FCC.





Technical Specifications

GALLAGHER CABINET A	AND GALLAGHER GBUS I/O ACCESSORY CA	ABINETS			
Housing	Height x Width x Depth		280 x 280 x 94 mm (11.02 x 11.02 x 3.7in)		
	Weight		1.9 kg (4.19lb)		
	Footprints		1		
Environmental Data	Temperature Range		-10° to +55° C (14°F to 131°F)		
	Humidity		95% non-condensing		
	Protection Rating		IP44		
Fire Resistance	Flame rating of plastic used in Cabinet		UL94/VO		
Compliance Standards	Compliance with other international star contact Gallagher for the latest list of ap installed in accordance with the Installat comply with international standards. RC	provals. All Gallagher products ion instructions to			
GALLAGHER DUAL CAB	INET				
Housing	Height x Width x Depth		620 x 372 x 150 mm (24.4 x 14.65 x 5.9 in)		
	Weight		6.8 kg (14.99 lb)		
	Footprints		2		
Material			Approx 1 mm thick steel (0.03 in)		
Humidity			90% non-condensing		
GALLAGHER POWER SU	JPPLY UNIT				
Construction	Mean Well AD-155A PSU with customiz Power Supply Installation Note for full sp		ed auxiliary power output. Please see the Dual Cabinet and		
Input Voltage			100 V AC - 240 V AC		
Output Voltage	Primary power output		13.8 V DC		
	Auxiliary isolated power output		13.5 V DC		
Current Range	Primary output current range: 0 - 7 A (or 8 A when secondary output not in use)				
	Auxiliary isolated output current range: 0 - 1 A				
	Battery output current range: 0 - 0.5 A				
Working Temperature			-10 °C to +50 °C (14 °F to 122 °F)		
Standards Compliance			EN55022 (EMC Standard)		
			EN60950 (Safety)		
Built in Protection	Short circuit/Over load/Over voltage pro	tection			
	Battery low and polarity protection				
Monitoring		Mains power and low battery monitoring via visual LED indicators and			
GALLAGHER PART NUM	IBERS				
C200104 Ft Dual Cabinet No PS Cool Grey		C200103	Ft Dual Cabinet No PS Charcoal		
C200107 Ft Dual Cab No PS Reinforced Cool Gry UI		C200108	Ft Dual Cab No PS Reinforced Charcoal UI		
C200105 Ft Dual Cabinet 8A PS Cool Grey		C200109	Ft Dual Cabinet 8A PS Charcoal		
C200001 Full Footprint Mounting Plate		C200440	Gallagher Power Supply		
C200002 Half Footprint Mounting Plate		C200610	Gallagher Tamper Board - Board Only		
200003 Controller 6000 I/O Mounting Plate		C200611	I/O Accessory Single Cabinet		

GALLAGHER WORLD HEADQUARTERS

Kahikatea Drive, Hamilton 3206 Private Bag 3026, Hamilton 3240 New Zealand

TEL: +64 7 838 9800

EMAIL: security@gallagher.com







REGIONAL OFFICES

New Zealand	+64 7 838 9800
Americas	+1 877 560 6308
Asia	+852 3468 5175
Australia	+61 3 9308 7722
India	+91 98 458 92920
Middle East	+971 4 5665834
South Africa	+27 11 974 4740
United Kinadom / Europe	+44 2476 64 1234

DISCLAMBER: Inis document gives Certain information approducts and/or services provided by Gallagher Group Limited or its related companies (referred to as "Gallagher Group"). This information is indicative only and is subject to change withou notice meaning it may be out of date at any given time. Although every commercially reasonable effort has been taken to ensure the quality and accuracy of the information, Gallagher Group makes not representation as to its accuracy or completeness and it should not be relied on as such. To the extent permitted by law, all express or implied, or other representations or warranties in relation to thinformation are expressly excluded. Neither Gallagher Group no any of its directors, employees or other representatives shall be responsible for any loss that you may incur, either directly or indirectly, arising from any use or decisions based on the information is subject to copyright owned by Gallagher Group is you may not sell it without permission. Gallagher Group is trademarks which are not the property of Gallagher Group, an acknowledged. Copyright © Gallagher Group Ltd. All right reserved.



